



SNUBBERS

HYDRAULICS



- 1/4" NPT
- 3/4" HEX SIZE
- 1-1/2" LENGTH



AVAILABLE IN BRASS OR STAINLESS STEEL
10,000 PSI BRASS; 15,000 PSI S.S.

GENERAL INFORMATION & APPLICATION

Eliminate pressure instrument failure due to hydraulic or pneumatic shock. Smooth out pressure impulses and fluctuations. Remove harmful solids from actuating fluid. Assure average pressure readings.

| BRASS SNUBBER | | | | | | | ORDER INFORMATION | |
|---------------|------|----------|--------|---|---------------|-----------|-------------------|-------|
| PSI | NPT | HEX SIZE | LENGTH | TYPE OF SERVICE | MICRON RATING | REFERENCE | STOCK NUMBER | PRICE |
| 10,000 | 1/4" | 3/4" | 1-1/2" | Oil (225 to 500S.S.U.) | 40-45 | 25BD | KS30100 | 8.27 |
| 10,000 | 1/4" | 3/4" | 1-1/2" | Water, L1.0:1 (30 to 225 S.S.U.) | 10 | 25BE | KS30200 | 8.27 |
| 10,000 | 1/4" | 3/4" | 1-1/2" | Vapor, Low Viscosity Fluids (under 30 S.S.U.) | 7 | 25BF | KS30300 | 8.27 |
| 10,000 | 1/4" | 3/4" | 1-1/2" | Air, Gasses | 2-5 | 25BG | KS30400 | 8.27 |

| STAINLESS STEEL SNUBBER | | | | | | | ORDER INFORMATION | |
|-------------------------|------|----------|--------|--|---------------|-----------|-------------------|-------|
| PSI | NPT | HEX SIZE | LENGTH | TYPE OF SERVICE | MICRON RATING | REFERENCE | STOCK NUMBER | PRICE |
| 15,000 | 1/4" | 3/4" | 1-1/2" | High Viscous Fluids (over 5000 S.S.U.) | 75 | 25SC | KS30500 | 10.39 |
| 15,000 | 1/4" | 3/4" | 1-1/2" | Oil (225-500 S.S.U.) | 40-45 | 25SD | KS30600 | 10.39 |
| 15,000 | 1/4" | 3/4" | 1-1/2" | Water, Lt. Oil (30-225 S.S.U.) | 10 | 25SE | KS30700 | 10.39 |

PRESSURE SWITCH

HYDRAULICS

MODEL PS-HI PRESSURE SWITCH

- Snap Action
- Field Adjustable
- Pneumatic / Hydraulic Application
- Din Connector
- 1/4" NPT Male Connector
- Air, Hydraulic (Pet Base), Lube Oil
- Life In Excess Of One Million Cycles

| STANDARD SPECIFICATIONS | |
|-----------------------------|--|
| Set Point Range: | 50 - 4200 PSI RISING (3.4 - 289 BAR) |
| Set Point Tolerance: | +5 PSI OR 5% (.34 BAR) |
| Maximum Operating Pressure: | 5000 PSI (334 BAR) |
| Proof Pressure: | 15000 PSI (1034 BAR) |
| Differential: | 5 - 10% |
| Current Rating: | 5 AMP |
| Media Connection: | 1/4" NPT MALE STEEL |
| Circuit Form: | SPDT |
| Electrical Connection: | DIN 43650A <small>PIN ASSIGNMENTS - #1 COMMON, #2 NORMALLY CLOSED, #3 NORMALLY OPEN, #4 NOT USED</small> |
| Diaphragm Material: | BUNA N = INDUSTRIAL HYDRAULIC/PNEUMATIC |

| PRESSURE SWITCH | | ORDER INFORMATION | |
|-----------------|--------------------|-------------------|--------|
| MODEL NUMBER | SET POINT RANGE | STOCK NUMBER | PRICE |
| WX-IC-550J/HR | 300 - 800 RISING | 5L00050 | 190.00 |
| WX-IC-2600J/HR | 1000 - 4200 RISING | 5L00100 | 166.00 |



GRAND RAPIDS

TOLL FREE 1-800-968-0188
PHONE: (616) 949-8844
FAX: (616) 949-6598

KALKASKA

TOLL FREE 1-800-355-4338
PHONE: (616) 258-4338
FAX: (616) 258-2696