

TEFLON HOSE WITH STAINLESS BRAID

HYDRAULICS



- HIGH & EXTREME TEMPERATURE RANGE
-100° TO 500°F
- PRESSURE RATING TO 3000 P.S.I. WITH A 4:1
SAFETY BURST FACTOR (TO 12,000 P.S.I.)
- EXCELLENT FOR HOT OILS, & STEAM, PURIFIED
WATER AND MOST CHEMICALS

MEDIUM PRESSURE TEFLON HOSE						ORDER INFORMATION	
HOSE I.D. (in.)	HOSE O.D. (in.)	WORKING PRESSURE	MIN. BURST PRESSURE	BEND RADIUS (in.)	REFERENCE	STOCK NUMBER	PRICE
3/16"	.31	1,500	10,000	2	4C14	GB00832	6.71
1/4"	.38	1,500	9,000	3	5C14	GB00833	7.06
5/16"	.45	1,500	8,000	4	6C14	GB00834	8.35
13/32"	.55	1,000	6,000	5.25	8C14	GB00835	10.69
1/2"	.65	800	6,000	6.5	10C14	GB00836	13.28
5/8"	.79	800	5,000	7.75	12C14	GB00837	15.54
7/8"	1.03	800	3,500	9	16C14	GB00838	22.64

BRASS FITTINGS FOR TEFLON/STAINLESS HOSE

HYDRAULICS



MALE PIPE

MALE PIPE FITTING			ORDER INFORMATION	
HOSE SIZE	THREAD SIZE	REFERENCE	STOCK NUMBER	PRICE
3/16"	1/8-27	4C14-2MPB	GA85470	9.78
5/16"	1/4-18	6C14-4MPB	GA85500	11.08
13/32"	3/8-18	8C14-6MPB	GA85520	11.83
1/2"	1/2-14	10C14-8MPB	GA85540	19.56
5/8"	3/4-14	12C14-12MPB	GA85545	22.82
7/8"	1-1/2-11	16C14-16MPB	GA85560	35.60



FEMALE SWIVEL
JIC

FEMALE SWIVEL			ORDER INFORMATION	
HOSE SIZE	THREAD	REFERENCE	STOCK NUMBER	PRICE
3/16"	7/16-20	4C14-4FJSXB	GA85570	7.22
5/16"	9/16-18	6C14-6FJSXB	GA85590	9.78
13/32"	3/4-16	8C14-8FJSXB	GA85600	10.50
1/2"	7/8-14	10C14-10FJSXB	GA85610	16.31
5/8"	1 1/16-12	12C14-12FJSXB	GA85620	21.62
7/8"	1 5/16-12	16C14-16FJSXB	GA85630	32.71

GRAND RAPIDS

TOLL FREE 1-800-968-0188
PHONE: (616) 949-8844
FAX: (616) 949-6598

KALKASKA

TOLL FREE 1-800-355-4338
PHONE: (616) 258-4338
FAX: (616) 258-2696